



Control:One

The Control:One is standard to every Sooloos system, and provides the interface for you to interact with your music. It features a high-contrast 17-inch LCD display, resistive touch panel, and CD mechanism for importing your music. The Control:One's machined aluminum chassis has integrated heatsinks, eliminating fans and making it completely silent. Connect your Control:One to your Sooloos system using the supplied Neutrik EtherCon connectors or any standard ethernet cable (CAT5/5e/6 with RJ-45 connectors).

Control:Bridge

The Control:Bridge provides all the features of the Control:One, but allows you to display the user interface on your Crestron panel, so you can enjoy the Sooloos experience anywhere you have a compatible device*. The rackmountable Control:Bridge works by providing a video feed of the user interface which is routed to your panel. In turn, touch information is captured and sent back to the Control:Bridge via IP or RS-232.

**Please contact Sooloos at sales@sooloos.com for a current list of compatible models.*



Control:Bridge Tech Specs:

Dimensions:

Size: 16.7" wide x 3.4" high x 9" deep
Weight: 12.8 pounds
Mount: 19" Rackmount

Connections:

Network: 1 Ethernet (RJ-45) or Neutrik EtherCon
Power: 115V/230V auto-sensing, IEC mains port
Video: Component, VGA, HDMI
Serial: 1 DB9 RS-232

Control:One Tech Specs:

Dimensions:

Size: 18" wide x 13.6" high x 7.3" deep
Weight: 23.6 pounds
Tilt: Adjusts from 0° (vertical) to 50° (tilted)

Connections:

Network: 1 Ethernet (RJ-45) or Neutrik EtherCon
Power: 1115V/230V switchable,
attached 3-prong power cable

LCD Display:

Size/Resolution: 17" diagonal/1280x1024 pixels
Brightness: 350 cdm2
Viewing Angle: 150°

Touch Panel:

Type: Analog resistive 5-wire
Activation Force: < 50g
Structure: Film/Glass
Lifetime Durability: 35 million touches

View from Behind:

