



DSP7200.2

Digital Signal Processing Active Loudspeaker System



Colour available via Meridian Select

The concept of the Digital Active DSP Loudspeaker, first brought to market by Meridian over two decades ago, provides the most accurate and effective path to high quality sound reproduction. The latest edition of our DSP7200.2 takes this technology to a new high, with a series of technological innovations that deliver superior performance in many areas.

The DSP7200.2 features the latest internal electronics and software combined with specialised power amplifiers. It also includes the Enhanced Bass Alignment (EBA) system, which ensures that low frequencies are time-aligned across the entire bass range. This provides the bottom-end extension benefits of porting, but retains the exact timing and coherence previously associated only with 'closed-box' designs.

The result is deep, tight bass and clarity coupled with clean, clear, audibly-superior low frequency transients.

In common with all Meridian's DSP Loudspeakers, DSP7200.2 uses digital signal processing both for crossover filtering and all other signal processing. DSP7200.2 features a sophisticated multi-amplifier active loudspeaker topology, in which each individual driver is powered by a dedicated amplifier channel.

Ultra-accurate DSP delivers crossover characteristics and precision that would be inconceivable for any passive, analogue system, for a level of driver integration that is otherwise unobtainable.

Additionally, individually powering each driver after the crossover system enhances dynamics, reduces distortion and provides idealised time-domain behaviour.

The DSP7200.2 benefits from original research at Meridian into digital filtering, featuring a special upsampling filter with especially impressive characteristics and no pre-echo.

Product Information

3½-way Digital Signal Processing (DSP) active loudspeaker system

Self-contained audio system with four custom drivers, amplifiers, digital converters, improved digital crossovers and advanced sound-shaping DSP technology

New improved-performance dual-magnet, semi-horn-loaded composite dome tweeter with silver voice coil.

Advanced DSP filtering "cleans up" older digital recordings, and new Enhanced Bass Alignment improves LF transient response

Horizontal centre channel unit includes unique Centre Elevation adjustment technology – raises the centre image for perfect movie enjoyment

SpeakerLink digital audio and control I/O interface via RJ45

Curved cabinet features advanced damping technology and "Meridium" metal/wood laminate for superb rigidity

Additional listener controls include volume, bass, treble tilt, listening axis, time-compensated balance, absolute phase, Enhanced Boundary Correction and other new features

Black and white piano lacquer finishes; other colours to order via the Meridian Select programme

Meridian Audio Limited

meridian-audio.com



The DSP7200.2HC horizontal ported design, designed for home theatre applications.

This 'apodising' filter is so effective that it can correct problems further up the chain – even including fixing faults in the original recording. As a result, conventional 44.1/48 kHz sampled CDs and DVDs sound astonishingly like high resolution recordings.

The DSP7200.2 accepts a digital feed directly from a Meridian controller, CD, DVD player or system controller, handling the highest resolution bitstreams, eliminating analogue speaker cabling and its associated losses, coloration, and clutter, while SpeakerLink allows it to be driven by a single, low-profile cable.

Meridian's DSP loudspeakers bring unique opportunities for optimization of driver/amplifier/enclosure systems, while giving listeners unprecedented control over music and cinema sound playback.

The DSP7200.2's four internal 150-watt amplifiers are of the same balanced-input, highcurrent design employed in the flagship DSP8000, with heat-sinking on the extruded back panel. Two amplifiers drive a pair of refined 8-inch, long-throw bass units with a new basket design, separately housed in their own optimised enclosure in the base of the loudspeaker system.

Meanwhile the 6-inch midrange unit is the same driver as that used in the DSP8000, employing a cone made from a uniquely light and stiff combination of polymers to deliver unparalleled transparency.

The new, high efficiency treble unit is a dual-magnet, semi-horn-loaded composite dome type with a silver voice coil. Both are driven by their own amplifiers and

operate from a second, completely separate enclosure above the bass/electronics module.

Whether in a two-channel system or as part of a multichannel home theatre array, the DSP7200.2 provides precision command of frequency balance, listening axis, time-compensated balance and master volume – all implemented utterly transparently.

The companion DSP7200.2HC horizontal centre-channel loudspeaker features breakthrough DSP technology, such as Centre Elevation adjustment, which employs results of the latest psychoacoustical research to vary the height of the audio image. Thanks to this unique, proprietary development, the loudspeaker may be placed beneath the screen in a home theatre installation, while the sonic image can be elevated to the centre of the screen image or to align with the main front loudspeakers as desired.

DSP7200.2 includes Meridian's SpeakerLink input/output interfacing architecture, featuring balanced drive and RJ45 connectors for simplicity and elegance of installation via simple, unobtrusive cabling. The DSP7200.2 cabinet, like that of the DSP8000, is crafted from Meridian's innovative 'Meridium', a multi-layered 'sandwich' of selected woods and metal, formed in curved, pressure-laminated panels that produce almost perfectly vibration- and resonance-free enclosures, for unmatched freedom from coloration. The exteriors of these unique cabinets are painstakingly finished in Meridian gloss piano lacquer black or white colours, with the full range of Meridian Select colours available to order.

Outline Technical Specification

Performance

- Frequency response in-room within 3dB from 30Hz to over 20kHz.
- Maximum output >112dB spl @ 1m on music material.
- Noise less than 15dB spl.
- Overall electronic distortion typically <0.02% at any frequency or level.

Inputs

- 1x phono digital input (S/PDIF)
- 1x balanced digital (AES/EBU) input on RJ45; 32kHz–96kHz sampling rates at up to 24 bit; MHR support. RJ45 input also carries RS232 and trigger.

Outputs

- 1x RJ45 with balanced digital audio and control for a second loudspeaker. Infra-red pickup for system automation.

Construction

- '3½-way' acoustic reflex system.
- Digital crossovers at 200Hz and 2.6kHz.
- 2 x 200mm long-throw bass drivers.
- 1 x 160mm polypropylene mid driver.
- 1 x 25mm composite-dome tweeter, silver wire, dual magnet, semi-horn-loaded.
- Gloss black or white piano-lacquer cabinet, other colours available to order.

Electronics

- FIFO memory buffer input for the lowest possible jitter from almost any source.
- Analogue gain & filtering with proprietary Meridian Class-A discrete amplification.
- Digital & conversion electronics utilise advanced surface-mount techniques and partitioned 6-layer printed-circuit boards.
- 4x 24-bit 128x oversampling D/A converters for maximum audio quality.
- 4x 150W/4Ω power amplifiers – one per driver (2xbass, 1xmid, 1xHF).

Dimensions:

- Vertical version: 1072 (42.25) H (no feet), 350/180 (13.75/7.1) W, 415/217 (16.5/8.5) D [base/top, mm (in)]
- HC version: 295 (11.6) H, 1060.5 (41.75), D 478.25 (18.8) max [mm/(in)]. Measure actual unit before specifying.

Weight:

- 55kg (121 lb) each (vertical version).
- 64kg (141 lb) (horizontal centre version)

Controls

- Rear-panel controls for Power On/Off. MSR+ and via SpeakerLink

Front display

- Eight-character display w/system lights

Power

- 20W standby, 920W max