



Quality redefined,
brilliant natural sound...



QUAD

IAG House, Sovereign Court, Ermine Business Park, Huntingdon, Cambs, PE29 6XU,UK
Tel: +44(0)1480 447700 Fax: +44(0)1480 431767 <http://www.quad-hifi.co.uk>
IAG reserve the right to alter design and specification without notice. All rights reserved © IAG Group Ltd.
Quad is a member of the International Audio Group.




Performance
series

QA-900, QD-900, QL-900

QUAD

the closest approach to the original sound

A History of Achievement



Since Peter Walker founded Quad in 1936, all Quad products have displayed originality in design, born from a full and proper understanding of every aspect of sound reproduction. A world leader in audio amplifier and electrostatic speaker design, Quad has, over the years, made a major advancements in the improvement of sound quality. This contribution has been recognised by awards from around the world including the Queen's Award for Technological Achievement in 1978 – the only one ever presented to an audio hi-fi equipment manufacturer.

Quad Performance Series

Leading the field of ESL design, having developed the world's first commercially successful electro-static loudspeaker in the 1950s, Quad has been recognised worldwide for manufacturing the finest hi-end loudspeakers. In keeping with its design philosophy of manufacturing high-end system solutions including Valve electronics, Solid state electronics and traditional audiophile loudspeaker systems and cables, Quad has combined British design and engineering with the industry's most efficient manufacturing facilities to create a multitude of products that are incomparable in terms of value and performance. The design technology and quality standards applied to Quad interconnects are the finest available. The level of refinement achievable with these digital and analogue interconnects will surprise you as they will significantly enhance your system's sonic performance, creating the closest approach to real sound.



QA-900


Performance Analogue Interconnect

Recommended for all analogue connections: CD/DVD Players, FM Tuners, Preamplifiers and Power amplifiers

Custom-designed using a twisted pair, symmetrical cable; Terminated with low noise, gold-plated twist-lock RCA connectors with gold-plated outer shield construction for maximum signal integrity; Uses two (2) Oxygen-Free, High Purity Copper (OFHC) conductors reinforced with an aluminium foil wrap

Specifications	
Resistance	0.013Ω/M
Inductance	1.3μH/M
Capacitance	56pF/M
Shielding	100%
Wire Gauge	14AWG
Gold Plating	24kgp
O/D	9.0mm
Sheath	Brown Interweave
Connection Type	Twist-lock

Section Drawing:



1. OFHC Conductor

2. Teflon™ FEP

3. Mylar™ Reinforced Aluminium Foil

4. Shield Drain Wire
5. Cotton Fibre


6. Impregnated Paper

7. Outer Jacket PVC

8. Protective Mesh

Available Lengths: 1.5m, 2.0m, 3.0m

Connectors:



QD-900


Performance Digital Interconnect

Recommended for high speed coaxial digital audio connections: CD / DVD / DAC Digital Output

Triple-shielded and terminated with gold-plated twist-lock contacts with RCA to RCA connections; Uses Oxygen-Free, High Purity Copper (OFHC) multi-strand centre conductor with uniform charge distribution, close tolerance impedance and strong mechanical protection

Specifications	
Resistance	0.018Ω/M
Inductance	1.39μH/M
Capacitance	51.3pF/M
Shielding	100%
Wire Gauge	17AWG
Gold Plating	24kgp
O/D	9.0mm
Sheath	Brown Interweave
Connection Type	Twist-lock

Section Drawing:



1. OFHC Conductor

2. Dielectric Foam

3. Braided Outer Conductor

4. Inner Jacket 80P PVC

5. Mylar™ Reinforced Aluminium Foil
6. Braided Screen


7. Inner Jacket 80P PVC

8. Outer Jacket PVC

9. Protective Mesh

Available Lengths: 1.5m, 2.5m, 3.0m

Connector:



QL-900


Performance Loudspeaker Cable

Recommended for high fidelity loudspeaker connections: Power Amplifier, Integrated Stereo Amplifier and Multi-Channel Amplification Systems

Excellent dielectric properties resulting in high bandwidth audio direct from the source; Uses two (2) multi-section wires with an Oxygen-Free, High Purity Copper (OFHC) conductor core and terminated with high precision 4mm gold-plated (OFHC) Twist-lock banana plugs for excellent security and seamless connectivity

Specifications	
Resistance	0.007Ω/M
Inductance	1.22μH/M
Capacitance	107.0pF/M
Shielding	100%
Wire Gauge	24AWG
Gold Plating	24kgp
O/D	9.0mm
Sheath	Brown Interweave
Connection Type	Twist-lock

Section Drawing:



1. OFHC Conductor

2. Insulation HDPE

3. Outer Jacket PVC

4. Protective Mesh

Available Lengths: 3.0m

Connectors:

