

| QUAD ESL SERIES                                                                                            |                                       |                                                      |  |                  |
|------------------------------------------------------------------------------------------------------------|---------------------------------------|------------------------------------------------------|--|------------------|
| MODEL                                                                                                      | SPECIFICATIONS                        |                                                      |  | RRP<br>(Inc GST) |
| <b>ESL-2905</b><br><br>   | Type                                  | Full-range Electrostatic                             |  | \$18,999.00      |
|                                                                                                            | Maximum Power Output                  | 2 N/m <sup>2</sup> at 2m on axis                     |  |                  |
|                                                                                                            | Sensitivity                           | 1.5 mbar per volt referred to 1m (= 86 dB/2.83V RMS) |  |                  |
|                                                                                                            | Impedance                             | 8 ohm nominal                                        |  |                  |
|                                                                                                            | Max continuous input voltage (RMS) -  | 10V                                                  |  |                  |
|                                                                                                            | 20Hz to 20kHz                         |                                                      |  |                  |
|                                                                                                            | Programme peak for undistorted output | 40V                                                  |  |                  |
|                                                                                                            | Permitted peak input                  | 55V                                                  |  |                  |
|                                                                                                            | Frequency response                    | 32Hz-21kHz (-6dB)                                    |  |                  |
|                                                                                                            | Panel elements                        | 6                                                    |  |                  |
|                                                                                                            | Power consumption                     | 6 Watts                                              |  |                  |
|                                                                                                            | Dimensions (H x W x D)                | 1430 x 695 x 385mm<br>(add 25 - 55mm for feet)       |  |                  |
|                                                                                                            | Weight                                | 41.6kg                                               |  |                  |
|                                                                                                            | Finish / Colours                      | Black                                                |  |                  |
|                                                                                                            |                                       | Classique                                            |  | \$19,999.00      |
| <b>ESL-2805</b><br><br> | Type                                  | Full-range Electrostatic                             |  | \$16,499.00      |
|                                                                                                            | Maximum Power Output                  | 2 N/m <sup>2</sup> at 2m on axis                     |  |                  |
|                                                                                                            | Sensitivity                           | 1.5 mbar per volt referred to 1m (= 86 dB/2.83V RMS) |  |                  |
|                                                                                                            | Impedance                             | 8 ohm nominal                                        |  |                  |
|                                                                                                            | Max continuous input voltage (RMS) -  | 10V                                                  |  |                  |
|                                                                                                            | 20Hz to 20kHz                         |                                                      |  |                  |
|                                                                                                            | Programme peak for undistorted output | 40V                                                  |  |                  |
|                                                                                                            | Permitted peak input                  | 55V                                                  |  |                  |
|                                                                                                            | Frequency response                    | 37Hz-21kHz (-6dB)                                    |  |                  |
|                                                                                                            | Panel Elements                        | 4                                                    |  |                  |
|                                                                                                            | Power consumption                     | 6 watts                                              |  |                  |
|                                                                                                            | Dimensions                            | 1040 x 695 x 385mm<br>(add 25-55mm for feet)         |  |                  |
|                                                                                                            | Weight                                | 34.8kg                                               |  |                  |
|                                                                                                            | Finish / Colours                      | Black                                                |  |                  |
|                                                                                                            |                                       | Classique                                            |  | \$17,999.00      |

| QUAD ESL SERIES continued                                                                          |                                       |                                                      |  |                  |
|----------------------------------------------------------------------------------------------------|---------------------------------------|------------------------------------------------------|--|------------------|
| MODEL                                                                                              | SPECIFICATIONS                        |                                                      |  | RRP<br>(Inc GST) |
| ESL-989<br><br>   | Type                                  | Full-range Electrostatic                             |  | \$13,999.00      |
|                                                                                                    | Maximum Power Output                  | 2 N/m <sup>2</sup> at 2m on axis                     |  |                  |
|                                                                                                    | Sensitivity                           | 1.4u bar per volt referred to 1m (= 86 dB/2.83V RMS) |  |                  |
|                                                                                                    | Impedance                             | 8 ohm nominal                                        |  |                  |
|                                                                                                    | Max continuous input voltage (RMS)    | 10V                                                  |  |                  |
|                                                                                                    | 20Hz to 20kHz                         |                                                      |  |                  |
|                                                                                                    | Programme peak for undistorted output | 40V                                                  |  |                  |
|                                                                                                    | Permitted peak input                  | 55V                                                  |  |                  |
|                                                                                                    | Axis band limits                      | -6dB at 35Hz 3 <sup>rd</sup> Order                   |  |                  |
|                                                                                                    | (low level)                           | -6dB >20kHz                                          |  |                  |
|                                                                                                    | Dimensions (H x W x D)                | 1335 x 670 x 315 (including 185mm base)              |  |                  |
|                                                                                                    | Weight                                | 25.3kg                                               |  |                  |
|                                                                                                    | Finish / Colours                      | Black                                                |  |                  |
|                                                                                                    |                                       | Noveau, Vintage (10 -12 weeks lead time)             |  | \$15,999.00      |
| ESL-988<br><br> | Type                                  | Full-range Electrostatic                             |  | \$10,999.00      |
|                                                                                                    | Maximum Power Output                  | 2 N/m <sup>2</sup> at 2m on axis                     |  |                  |
|                                                                                                    | Sensitivity                           | 1.4u bar per volt referred to 1m (= 86 dB/2.83V RMS) |  |                  |
|                                                                                                    | Impedance                             | 8 ohm nominal                                        |  |                  |
|                                                                                                    | Max continuous input voltage (RMS)    | 10V                                                  |  |                  |
|                                                                                                    | 20Hz to 20kHz                         |                                                      |  |                  |
|                                                                                                    | Programme peak for undistorted output | 40V                                                  |  |                  |
|                                                                                                    | Permitted peak input                  | 55V                                                  |  |                  |
|                                                                                                    | Axis band limits                      | -6dB at 35Hz 3 <sup>rd</sup> Order                   |  |                  |
|                                                                                                    | (low level)                           | -6dB >20kHz                                          |  |                  |
|                                                                                                    | Dimensions (H x W x D)                | 940 x 670 x 315mm (including 185mm base)             |  |                  |
|                                                                                                    | Weight                                | 20.5kg                                               |  |                  |
|                                                                                                    | Finish / Colours                      | Black                                                |  |                  |
|                                                                                                    |                                       | Noveau, Vintage (10 -12 weeks lead time)             |  | \$13,999.00      |

| QUAD L2 SERIES LOUDSPEAKERS                                                                 |                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                    |  |                  |
|---------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|------------------|
| MODEL                                                                                       | SPECIFICATIONS                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                    |  | RRP<br>(Inc GST) |
| 22L2<br>   | Transducer Complement<br>Cone Bass Driver<br>Cone Bass / Mid Driver<br>Soft Dome Tweeter<br>Nominal Impedance<br>Frequency Response (-6dB)<br>Upper Limit (-10dB)<br>Power Handling - Continuous<br>Recommended Amplifier<br>Enclosure type<br>System Fb<br>Crossover Frequency(s)<br>Construction<br>Dimensions (H x W x D)<br>Finishes / Colours | 2.5 Way<br>6.5" (170mm)<br>6.5" (170mm)<br>25mm / 1"<br>6 Ohms<br>30Hz - 28kHz<br>32kHz<br>150W<br>50-300W<br>Ported / Sealed Mid<br>35Hz<br>150Hz, 3kHz<br>15/25mm MDF<br>850 x 205 x 278 mm<br>Black, Rosewood, Maple,<br>Cherry, Birdseye Maple |  | \$2,999.00       |
| 21L2<br> | Transducer Complement<br>Cone Bass Driver<br>Cone Bass / Mid Driver<br>Soft Dome Tweeter<br>Nominal Impedance<br>Frequency Response (-6dB)<br>Upper Limit (-10dB)<br>Power Handling - Continuous<br>Recommended Amplifier<br>Enclosure type<br>System Fb<br>Crossover Frequency(s)<br>Construction<br>Dimensions (H x W x D)<br>Finishes / Colours | 2 Way<br>6.5" (170mm)<br>n/a<br>1" (25mm)<br>6 Ohms<br>35Hz - 28kHz<br>32kHz<br>125W<br>40-200W<br>Ported<br>40Hz<br>2.2kHz<br>15/25mm MDF<br>780 x 205 x 263 mm<br>Black, Rosewood, Maple,<br>Cherry, Birdseye Maple                              |  | \$2,699.00       |

| QUAD L2 SERIES LOUDSPEAKERS continued                                                           |                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                       |  |                  |
|-------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|------------------|
| MODEL                                                                                           | SPECIFICATIONS                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                       |  | RRP<br>(Inc GST) |
| 12L2<br><br>   | Transducer Complement<br>Cone Bass Driver<br>Cone Bass / Mid Driver<br>Soft Dome Tweeter<br>Nominal Impedance<br>Frequency Response (-6dB)<br>Upper Limit (-10dB)<br>Power Handling - Continuous<br>Recommended Amplifier<br>Enclosure type<br>System Fb<br>Crossover Frequency(s)<br>Construction<br>Dimensions (H x W x D)<br>Finishes / Colours | 2 Way<br>6.5" (170mm)<br>n/a<br>1" (25mm)<br>6 Ohms<br>45Hz - 28kHz<br>32kHz<br>100W<br>30-200W<br>Ported<br>50Hz<br>2.2kHz<br>15/25mm MDF<br>330 x 205 x 253 mm<br>Black, Rosewood, Maple,<br>Cherry, Birdseye Maple |  | \$1,499.00       |
| 11L2<br><br> | Transducer Complement<br>Cone Bass Driver<br>Cone Bass / Mid Driver<br>Soft Dome Tweeter<br>Nominal Impedance<br>Frequency Response (-6dB)<br>Upper Limit (-10dB)<br>Power Handling - Continuous<br>Recommended Amplifier<br>Enclosure type<br>System Fb<br>Crossover Frequency(s)<br>Construction<br>Dimensions (H x W x D)<br>Finishes / Colours | 2 Way<br>5" (125mm)<br>n/a<br>1" (25mm)<br>6 Ohms<br>45Hz - 28kHz<br>32kHz<br>85W<br>30-150W<br>Ported<br>55Hz<br>2.2kHz<br>15/25mm MDF<br>310 x 190 x 243 mm<br>Black, Rosewood, Maple,<br>Cherry, Birdseye Maple    |  | \$1,149.00       |

| QUAD L2 SERIES LOUDSPEAKERS continued                                                                |                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                        |  |                  |
|------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|------------------|
| MODEL                                                                                                | SPECIFICATIONS                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                        |  | RRP<br>(Inc GST) |
| 9L2<br><br>         | Transducer Complement<br>Cone Bass Driver<br>Cone Bass / Mid Driver<br>Soft Dome Tweeter<br>Nominal Impedance<br>Frequency Response (-6dB)<br>Upper Limit (-10dB)<br>Power Handling - Continuous<br>Recommended Amplifier<br>Enclosure type<br>System Fb<br>Crossover Frequency(s)<br>Construction<br>Dimensions (H x W x D)<br>Finishes / Colours | 2 Way<br>4" (100mm)<br>n/a<br>1" (25mm)<br>6 Ohms<br>50Hz - 28kHz<br>32kHz<br>75W<br>30-120W<br>Ported<br>60Hz<br>2.0kHz<br>15/25mm MDF<br>248 x 152 x 205 mm<br>Black, Rosewood, Maple,<br>Cherry, Birdseye Maple     |  | \$899.00         |
| L2 Center<br><br> | Transducer Complement<br>Cone Bass Driver<br>Cone Bass / Mid Driver<br>Soft Dome Tweeter<br>Nominal Impedance<br>Frequency Response (-6dB)<br>Upper Limit (-10dB)<br>Power Handling - Continuous<br>Recommended Amplifier<br>Enclosure type<br>System Fb<br>Crossover Frequency(s)<br>Construction<br>Dimensions (H x W x D)<br>Finishes / Colours | 2 Way<br>2 x 5" (125mm)<br>n/a<br>1" (25mm)<br>6 Ohms<br>90Hz - 28kHz<br>32kHz<br>70W<br>30-120W<br>Sealed<br>60Hz<br>2.0kHz<br>15/25mm MDF<br>163 x 428 x 206 mm<br>Black, Rosewood, Maple,<br>Cherry, Birdseye Maple |  | \$999.00         |

| QUAD L2 SERIES LOUDSPEAKERS continued |                                                                                   |                                                   |  |                  |
|---------------------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------|--|------------------|
| MODEL                                 | SPECIFICATIONS                                                                    |                                                   |  | RRP<br>(Inc GST) |
| L2 Subwoofer                          |  |                                                   |  | \$2,699.00       |
|                                       | Transducer Complement                                                             | Single Tri-lam driver                             |  |                  |
|                                       | Cone Bass Driver                                                                  | 12" (300mm)                                       |  |                  |
|                                       | Amplifier Power Output                                                            | 300W RMS                                          |  |                  |
|                                       | Line Input Sensitivity                                                            | 250mV for 100W output                             |  |                  |
|                                       | Input Impedance                                                                   | 10K line input                                    |  |                  |
|                                       | Frequency Response (Boundary)                                                     | 25Hz to 95Hz                                      |  |                  |
|                                       | Lower Limit (-10dB)                                                               | 32Hz                                              |  |                  |
|                                       | Avg max Output @1m                                                                | 113dB                                             |  |                  |
|                                       | Crossover Range                                                                   | 35 to 85Hz                                        |  |                  |
|                                       | Enclosure type                                                                    | Sealed                                            |  |                  |
|                                       | Dimensions (H x W x D)                                                            | 535 x 345 x 465mm                                 |  |                  |
|                                       | Finishes / Colours                                                                | Black, Rosewood, Maple,<br>Cherry, Birdseye Maple |  |                  |

| QUAD L-ACTIVE SERIES LOUDSPEAKERS                                                                 |                                                                                                                                                                                                                                         |                                                                                                                                                                                                           |  |                  |
|---------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|------------------|
| MODEL                                                                                             | SPECIFICATIONS                                                                                                                                                                                                                          |                                                                                                                                                                                                           |  | RRP<br>(Inc GST) |
| 12L Active<br>   | Amplifier<br>Cone Bass Driver<br>Cone Bass / Mid Driver<br>Soft Dome Tweeter<br>Maximum SPL<br>Frequency Response (-3dB)<br>Frequency Response (-10dB)<br>Crossover Frequency<br>Dimensions (H x W x D)<br>Weight<br>Available Finishes | 60W / 40W dual amplifiers<br>6.5" (170mm)<br>N/A<br>1" (25mm)<br>110dB<br>55Hz to 20kHz<br>45Hz to 24kHz<br>2.2kHz<br>357 x 205 x 308mm<br>9.7kg<br>Black, Cherry, Birdseye Maple, Silver                 |  | \$2,499.00       |
| 11L Active<br> | Amplifier<br>Cone Bass Driver<br>Cone Bass / Mid Driver<br>Soft Dome Tweeter<br>Maximum SPL<br>Frequency Response (-3dB)<br>Frequency Response (-10dB)<br>Crossover Frequency<br>Dimensions (H x W x D)<br>Weight<br>Available Finishes | 60W/40W dual amplifiers<br>5" (125mm)<br>N/A<br>1" (25mm)<br>102dB<br>70Hz to 20kHz<br>50Hz to 20kHz<br>2.2kHz<br>326 x 190 x 284mm<br>8.2kg<br>Black, Cherry, Birdseye Maple, Silver                     |  | \$1,899.00       |
| 9L Active<br>  | Amplifier<br>Cone Bass Driver<br>Cone Bass / Mid Driver<br>Soft Dome Tweeter<br>Frequency Response (+/-3dB)<br>Maximum SPL<br>Connectivity - Inputs<br>Remote Control<br>Dimensions (H x W x D)<br>Weight<br>Available Finishes         | Total 60W<br>4" (100mm)<br>N/A<br>1" (25mm)<br>50Hz - 21kHz<br>105dB<br>3.5mm Stero Jack, RCA Phono, USB<br>Included<br>248 x 152 x 237mm<br>5.3kg<br>Yellow, Pink, Purple, Grey, Green, Red, Blue, Black |  | \$999.00         |
| 9L Active Table Stand                                                                             | Available Finishes                                                                                                                                                                                                                      | Dark Grey only                                                                                                                                                                                            |  | \$169.00         |

| QUAD L-ITE SERIES LOUDSPEAKERS                                                                                |                                                                                                                                                                                                                                                        |                                                                                                                                                               |  |                  |
|---------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|--|------------------|
| MODEL                                                                                                         | SPECIFICATIONS                                                                                                                                                                                                                                         |                                                                                                                                                               |  | RRP<br>(Inc GST) |
| <b>L-ite 5.1 System</b><br>  | <b>2 pairs x L-ite Satellites</b><br><b>1 x L-ite Center</b><br><b>1 x L-ite Subwoofer</b>                                                                                                                                                             |                                                                                                                                                               |  | \$3,499.00       |
| <b>L-ite Satellite</b><br>   | Cone Bass Driver<br>Cone Bass / Mid Driver<br>Soft Dome Tweeter<br>Nominal Impedance<br>Sensitivity (2.83V @ 1m)<br>Frequency Response<br>Recommended Amplifier<br>Frequency Fb<br>Crossover Frequency<br>Dimensions (H x W x D)<br>Finishes / Colours | 4" (100mm)<br>N/A<br>1" (25mm)<br>6 Ohms<br>86dB<br>70Hz - 24kHz<br>30 -120W<br>70Hz<br>2.2kHz<br>225 x 135 x 160mm<br>Black, Rosewood, Cherry,<br>Silver     |  | \$699.00         |
| <b>L-ite Center</b><br>    | Cone Bass Driver<br>Cone Bass / Mid Driver<br>Soft Dome Tweeter<br>Nominal Impedance<br>Sensitivity (2.83V @ 1m)<br>Frequency Response<br>Recommended Amplifier<br>Frequency Fb<br>Crossover Frequency<br>Dimensions (H x W x D)<br>Finishes / Colours | 2 x 4" (100mm)<br>N/A<br>1" (25mm)<br>6 Ohms<br>87dB<br>80Hz - 24kHz<br>30 -150W<br>75Hz<br>2.5kHz<br>135 x 340 x 160mm<br>Black, Rosewood, Cherry,<br>Silver |  | \$649.00         |
| <b>L-ite Subwoofer</b><br> | Cone Bass Driver<br>Amplifier Power Output<br>Line Input Sensitivity<br>Input Impedance<br>Frequency Response (Boundary)<br>Max Output<br>Dimensions (H x W x D)<br>Finishes / Colours                                                                 | 10" (250mm)<br>300W RMS<br>250mV for 100W<br>10K Ohms (Line input)<br>25Hz - 95Hz<br>108dB<br>485 x 288 x 425mm<br>Black, Rosewood, Cherry,<br>Silver         |  | \$1,999.00       |

| QUAD VALVE SERIES                                                                                                             |                                                                                                                                                                                                                                 |                                                                                                                                                                                                       |  |                  |
|-------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|------------------|
| MODEL                                                                                                                         | SPECIFICATIONS                                                                                                                                                                                                                  |                                                                                                                                                                                                       |  | RRP<br>(Inc GST) |
| <b>QII-80 Mono Power Amps</b><br><br>        | Power Output<br>Total Harmonic Distortion @ 700Hz<br>Residual hum and noise<br>Frequency Response<br>Damping Factor<br>Power Consumption<br>Loudspeaker taps<br>Input Valves<br>Output Valves<br>Rectifier Valve<br>Sensitivity | 80W RMS<br>0.3% at 40W<br>0.5% at 80W<br>Better than -94dB<br>10Hz to 30kHz (+0dB/-0.5dB)<br>16 @ 1kHz<br>180W maximum<br>4 Ohm and 8 Ohm<br>2 x 6SL7<br>4 x KT88<br>1 x 6SN7<br>1V RMS               |  | \$15,999.00      |
| <b>QII-40 Mono Power Amps</b><br><br>      | Power Output<br>Total Harmonic Distortion @ 700Hz<br>Residual hum and noise<br>Frequency Response<br>Damping Factor<br>Power Consumption<br>Loudspeaker taps<br>Input Valves<br>Output Valves<br>Rectifier Valve<br>Sensitivity | 40W RMS<br>0.3% at 40W<br>0.03% at 1W<br>Better than -80dB<br>10Hz to 30kHz (+0dB/-0.5dB)<br>20 @ 700Hz (ref. 8 ohm)<br>180W maximum<br>4 Ohm and 8 Ohm<br>2 x 6SH7<br>2 x KT88<br>1 x 5U4G<br>1V RMS |  | \$6,699.00       |
| <b>QII-Classic Mono Power Amps</b><br><br> | Power Output<br>Total Harmonic Distortion @ 700Hz<br>Residual hum and noise<br>Frequency response<br>Damping Factor<br>Power Consumption<br>Loudspeaker Taps<br>Input valves<br>Output valves<br>Rectifier valve<br>Sensitivity | 15W RMS<br>0.3% @ 12W<br>better than -90dB<br>10Hz - 20kHz (+0.2dB)<br>11.75 @ 700Hz<br>90Va maximum<br>8 Ohm<br>2 x EF86<br>2 x KT66<br>1 x GZ34<br>1.4V RMS                                         |  | \$4,899.00       |

| QUAD VALVE SERIES continued                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |  |  |                  |
|--------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|------------------|
| MODEL                                                                                                              | SPECIFICATIONS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |  |  | RRP<br>(Inc GST) |
| QC-24 Valve Pre-Amp<br>           | Inputs (line level) 5<br>Inputs (buffered tape loops) 2<br>Valve complement 1 x 6111 twin triode<br>Total Harmonic Distortion < 0.2%<br>@ 1V RMS 0.02% @ 1W<br>Frequency Response 5Hz to 50kHz (+0/-0.5dB)<br>Hum and Noise > -80dB<br>Line stage gain 15dB<br>Recommended minimum load 50k ohms<br>Phono stage Optional                                                                                                                                                                                                                                                   |  |  | \$1,649.00       |
| QC-24P Phono Stage<br>          | Valve complement 4 x 6111 twin triode<br>Total Harmonic Distortion < 0.08% (A-weighted)<br>Hum and Noise Better than 60dB<br>Input Impedance - Moving Magnet 47ohms<br>Input Impedance - Moving Coil# 10 ohms<br>Stage Gain - High Sensitivity 1.3mV (MM)/130uV (MC)<br>Stage Gain - Medium Sensitivity 2.6mV (MM) / 260uV (MC)<br>Stage Gain - Low Sensitivity 5.2mV (MM) / 520uV (MC)<br>Nominal Output Level (ref 5.2mV, MM, Low) 1V<br>Inputs Selectable MM/MC cartridge<br>Outputs 1 x Fixed line level,<br>1 x Variable line level<br>Power Consumption 15VA maximum |  |  | \$2,999.00       |
| QC-24 Optional Phono Board<br>  | Optional Solid-State Phono Stage which can be added on when purchasing QC-24, or at a later stage. Must be installed by a Authorized Quad Service Representative                                                                                                                                                                                                                                                                                                                                                                                                           |  |  | \$499.00         |
| QII -Classic Integrated Amp<br> | Output Power 25W per Channel (8 ohm)<br>Total Harmonic Distortion 0.06% @ 15W (700Hz)<br>Frequency Response 20Hz - 20kHz (+0dB/-0.5dB)<br>Crosstalk Better than 75dB<br>Gain 34dB<br>Noise -98dB (275mV input)<br>Inputs 3 x Line Level<br>1 x MM/MC Phono (selectable)<br>1 x Tape<br>Valve Complement 4 x KT66, 4 x ECC88, 2 x ECC83                                                                                                                                                                                                                                     |  |  | \$9,499.00       |

| QUAD 99 SERIES ELECTRONICS                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                                                                         |  |                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|------------------|
| MODEL                                                                                                                                                                                                                                                                                                       | SPECIFICATIONS                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                         |  | RRP<br>(Inc GST) |
| <b>909 Stereo Power Amp</b><br><br><br><br><br><br>      | Maximum Power Output<br><br>Maximum Output Current<br><br>Total Harmonic Distortion<br><br>Input Sensitivity (phono)<br><br>Output Impedance<br><br>DC Offset Voltage<br><br>Frequency Response<br><br>Crosstalk at 1kHz<br><br>Signal to Noise ratio (70W)<br><br>Dimensions (H x W x D)<br><br>Available Finishes | 140W RMS (8ohms),<br>250W RMS (4ohms)<br><br>11 Amps peak each channel<br><br>0.02% (100W into 8Ohms; 20Hz - 20kHz)<br><br>775mV<br><br>1.5uH parallel with 0.05 Ohms<br><br>less than 10mV<br><br>13Hz to 40kHz (+0dB/-1dB)<br><br>-90dB at 1kHz<br><br>108dB (20Hz to 20kHz)<br><br>140 x 321 x 240mm<br><br>Black, Classique, Silver |  | \$2,999.00       |
| <b>99 Stereo Power Amp</b><br><br><br><br><br><br> | Maximum Power Output<br><br>Maximum Output Current<br><br>Total Harmonic Distortion<br><br>Input Sensitivity (phono)<br><br>Output Impedance<br><br>DC Offset Voltage<br><br>Frequency Response<br><br>Signal to Noise ratio (70W)<br><br>Dimensions (H x W x D)<br><br>Available Finishes                          | 90W RMS (8ohms),<br>120W RMS (4ohms)<br><br>11 Amps peak each channel<br><br>0.05% (70W into 8Ohms; 20Hz - 20kHz)<br><br>775mV<br><br>1.5uH parallel with 0.05 Ohms<br><br>less than 10mV<br><br>3Hz to 50kHz (+0dB/-3dB)<br><br>110dB (20Hz to 20kHz)<br><br>70 x 321 x 310mm<br><br>Black, Classique, Silver                          |  | \$1,499.00       |
| <b>99 Mono Power Amps</b><br><br><br><br><br><br>  | Maximum Power Output<br><br>Maximum Output Current<br><br>Total Harmonic Distortion<br><br>Input Sensitivity (phono)<br><br>Output Impedance<br><br>DC Offset Voltage<br><br>Frequency Response<br><br>Signal to Noise ratio (70W)<br><br>Dimensions (H x W x D)<br><br>Available Finishes                          | 150W RMS (8ohms),<br>220W RMS (4ohms)<br><br>11 Amps peak each channel<br><br>0.05% (70W into 8Ohms; 20Hz - 20kHz)<br><br>775mV<br><br>1.5uH parallel with 0.05 Ohms<br><br>less than 10mV<br><br>3Hz to 50kHz (+0dB/-3dB)<br><br>110dB (20Hz to 20kHz)<br><br>70 x 321 x 310mm<br><br>Black, Classique, Silver                         |  | \$3,099.00       |

| QUAD 99 SERIES ELECTRONICS continued                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                         |  |                  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|------------------|
| MODEL                                                                                                                                                                                                                                                                                                      | SPECIFICATIONS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                         |  | RRP<br>(Inc GST) |
| <b>99 Pre-Amp</b><br><br><br><br><br><br>             | 3 Aux & tape inputs - Sensitivity<br>3 Aux & tape inputs - Signal to Noise ratio<br>3 Aux & tape inputs - Distortion<br>Phono inputs MM (MC) - Sensitivity<br>Phono inputs MM (MC) - Signal to Noise ratio<br>Phono inputs MM (MC) - Distortion<br>Pre-Amp output - Level<br>Pre-Amp output - Source Impedance<br>Ampbus output - Level<br>Ampbus output - Source impedance<br>Tape Output - Level<br>Tape Output - Source impedance<br>Frequency response (except MM/MC)<br>Frequency response MM/MC<br>Dimensions (H x W x D)<br>Available Finishes | 100, 300 or 775mV<br>>97dB (A) ref. 775mV<br><0.002%<br>1, 3, or 7.75mV (100, 300 or 775 uV)<br>78dB (A) ref. 775mV (775uV)<br><0.005% (0.01%)<br>775mV (3.3V maximum)<br>100Ohms<br>2V (8V maximum)<br>20 Ohms<br>100, 300, or 775mV (10V maximum)<br>330 Ohms<br>10Hz to 20kHz, (+0dB/-0.3dB), 3Hz to 56kHz (+0dB/-3dB)<br>20Hz to 20kHz, (+0.5dB/-0.5dB), 7Hz to 53kHz (+0.5dB/-3dB)<br>70 x 321 x 310mm<br>Black, Classique, Silver |  | \$1,899.00       |
| <b>99 CDP-2 CD Player</b><br><br><br><br><br><br> | Max. Line Output Level (RCA)<br>Max Output Level (QuadLink)<br>Frequency Response<br>Total Harmonic Distortion<br>Signal to Noise ratio (S/N)<br>Crosstalk<br>Gain Error<br>D/A convertor Maximum Resolution<br>D/A convertor Maximum Sampling Resolution<br>Digital Audio Outputs<br>Digital Audio Inputs<br>Disc Compatibility<br>Dimensions (H x W x D)<br>Available Finishes                                                                                                                                                                      | 2.4V RMS<br>5.3V RMS (balanced)<br>20Hz to 20kHz(+0dB/-0.5dB)<br>0.002% at 1kHz<br>110dB, 24bit (20Hz – 20kHz)<br>95dB, 16bit (20Hz – 20kHz)<br>-100dB at 1kHz<br>0.5dB (@-90dB, 500Hz)<br>24bit<br>192kHz<br>Optical TosLink SPDIF<br>3 x RCA Coax 75ohm SPDIF,<br>3 x Optical TosLink SPDIF<br>CD-DA Conventional Audio, CD-R<br>Recordable (finalised and unfinalised)<br>80 x 321 x 310mm<br>Black, Classique, Silver               |  | \$2,499.00       |

| QUAD 99 SERIES ELECTRONICS continued                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |  |  |                  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|------------------|
| MODEL                                                                                                                                                                                                                                                                                               | SPECIFICATIONS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |  | RRP<br>(Inc GST) |
| <b>99CD-S CD Player</b><br><br><br><br><br><br>  | Max. Line Output Level (RCA) 2.4V RMS<br>Max Output Level (QuadLink) 5.3V RMS (balanced)<br>Frequency Response 20Hz to 20kHz(+0dB/-0.5dB)<br>Total Harmonic Distortion 0.002% at 1kHz<br>Signal to Noise ratio (S/N) 110dB, 24bit (20Hz - 20kHz)<br>95dB, 16bit (20Hz - 20kHz)<br>Crosstalk -100dB at 1kHz<br>Gain Error 0.5dB (@-90dB, 500Hz)<br>D/A convertor Maximum Resolution 24bit<br>D/A convertor Maximum Sampling Resolution 192kHz<br>Digital Audio Outputs Optical TosLink SPDIF<br>CD-DA Conventional Audio, CD-R Recordable (finalised and unfinalised)<br>Disc Compatibility<br>Dimensions (H x W x D) 80 x 321 x 310mm<br>Available Finishes Black, Classique, Silver |  |  | \$1,699.00       |
| <b>99 FM Tuner</b><br><br><br><br><br><br> | Tuning Range 880 to 108MHz<br>Channel Spacing 50kHz<br>Sensitivity (30dB quieting) Mono 8 dBuV<br>Sensitivity (50dB quieting) Mono 18dBuV, Stereo 18 dBuV<br>Signal to Noise ratio (1mV, 1kHz) Mono 72dB (A), Stereo 67dB (A)<br>Distortion (1kHz, 25kHz deviation) Mono, 0.03%, Stereo 0.05%<br>Capture Ratio 1.5dB<br>IF rejection >100dB<br>AM Suppression >60dB<br>Image Rejection >80dB<br>Pilot tone Suppression >60dB<br>Cross-talk -40dB at 1kHz<br>De-emphasis 50uS or 75uS<br>Aerial input 2 x 75Ohms un-balanced<br>Dimensions (H x W x D) 70 x 321 x 310mm<br>Available Finishes Black, Classique, Silver                                                                |  |  | \$1,799.00       |

| QUAD 99 SERIES ELECTRONICS continued                                                                          |                                                                                                          |  |  |                  |
|---------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|--|--|------------------|
| MODEL                                                                                                         | SPECIFICATIONS                                                                                           |  |  | RRP<br>(Inc GST) |
| 99 SERIES AUDIO RACK<br><br> | <b>Custom 99 Series Audio System Rack (Black Only)<br/>including Black Tempered Glass with Quad Logo</b> |  |  | \$999.00         |



QUAD

| QUAD CABLE                                                                                                           |                                                                                                                                                                                                                                                                                                                                                                              |  |  |                                    |
|----------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|------------------------------------|
| MODEL                                                                                                                | SPECIFICATIONS                                                                                                                                                                                                                                                                                                                                                               |  |  | RRP<br>(Inc GST)                   |
| QA-900 Analogue<br>Interconnect<br> | Custom-designed using a twisted pair, diameter round cable. Terminated with high flux, low noise, gold-plated twist-lock RCA connectors with gold-plated outer shield construction for maximum signal integrity. Uses two Oxygen Free, High Purity Copper (OFHC), conductors re-inforced with an aluminium foil wrap.<br><br><div>1.5m</div> <div>2.0m</div> <div>3.0m</div> |  |  | \$819.00<br>\$899.00<br>\$1,049.00 |
| QD-900 Digital<br>Interconnect<br> | Triple-shielded and terminated with gold-plated twist-lock contacts with RCA to RCA connections. Uses 100% Oxygen Free, High Purity Copper (OFHC), multi-strand centre conductor with uniform charging, tight impedance and strong protection.<br><br><div>1.5m</div> <div>2.0m</div> <div>3.0m</div>                                                                        |  |  | \$429.00<br>\$489.00<br>\$579.00   |
| QL-900 Loudspeaker<br>Cable<br>   | Excellent dielectric properties resulting in high bandwidth audio direct from the source. Uses two multi-section wires with an Oxygen Free, High Purity Copper (OFHC) conductor core and terminated with high precision 4mm gold-plated twist-lock banana plugs for excellent security and seamless connectivity.<br><br><div>3.0m</div>                                     |  |  | \$1,099.00                         |

